



01/14/00

10580 U.S. PTO

# UTILITY PATENT APPLICATION TRANSMITTAL

(Only for new nonprovisional applications under 37 CFR 1.53(b))

Attorney Docket No.

862.3206

First Named Inventor or Application Identifier

HITOSHI YANAGAWA

Express Mail Label No.

## APPLICATION ELEMENTS

See MPEP chapter 600 concerning utility patent application contents.

## ADDRESS TO:

Assistant Commissioner for Patents  
Box Patent Application  
Washington, DC 20231

1. ☐ Fee Transmittal Form  
(Submit an original, and a duplicate for fee processing)
2. ☒ Specification Total Pages
3. ☒ Drawings (35 USC 113) Total Sheets
4. ☒ Oath or Declaration Total Pages
- a. ☐ Newly executed (original or copy)
- b. ☒ Unexecuted for information purposes
- c. ☐ Copy from a prior application (37 CFR 1.63(d))  
(for continuation/divisional with Box 17 completed)  
[Note Box 5 below]
- i. ☐ DELETION OF INVENTOR(S)  
Signed Statement attached deleting  
inventor(s) named in the prior application, see  
37 CFR 1.63(d)(2) and 1.33(b).
5. ☐ Incorporation By Reference (useable if Box 4c is checked)  
The entire disclosure of the prior application, from which a copy of  
the oath or declaration is supplied under Box 4c, is considered as  
being part of the disclosure of the accompanying application and is  
hereby incorporated by reference therein.

6. ☐ Microfiche Computer Program (Appendix)
7. Nucleotide and/or Amino Acid Sequence Submission  
(if applicable, all necessary)
- a. ☐ Computer Readable Copy
- b. ☐ Paper Copy (identical to computer copy)
- c. ☐ Statement verifying identity of above copies

## ACCOMPANYING APPLICATION PARTS

8. ☐ Assignment Papers (cover sheet & document(s))
9. ☐ 37 CFR 3.73(b) Statement ☐ Power of Attorney  
(when there is an assignee)
10. ☐ English Translation Document (if applicable)
11. ☐ Information Disclosure ☐ Copies of IDS  
Statement (IDS)/PTO-1449 Citations
12. ☐ Preliminary Amendment
13. ☒ Return Receipt Postcard (MPEP 503)  
(Should be specifically itemized)
14. ☐ Small Entity ☐ Statement filed in prior application  
Statement(s) Status still proper and desired
15. ☐ Certified Copy of Priority Document(s)  
(if foreign priority is claimed)
16. ☐ Other: \_\_\_\_\_

17. If a CONTINUING APPLICATION, check appropriate box and supply the requisite information:

☐ Continuation ☐ Divisional ☐ Continuation-in-part (CIP) of prior application No. \_\_\_\_/\_\_\_\_

## 18. CORRESPONDENCE ADDRESS

☒ Customer Number or Bar Code Label

05514

(Insert Customer No. or Attach bar code label here)

or ☐ Correspondence address below

NAME

Address

City

State

Zip Code

Country

Telephone

Fax



CLAIMS	(1) FOR	(2) NUMBER FILED	(3) NUMBER EXTRA	(4) RATE	(5) CALCULATIONS
	TOTAL CLAIMS (37 CFR 1.16(c))	31-20 =	11	X \$ 18.00 =	\$198.00
	INDEPENDENT CLAIMS (37 CFR 1.16(b))	6-3 =	3	X \$ 78.00 =	\$234.00
	MULTIPLE DEPENDENT CLAIMS (if applicable) (37 CFR 1.16(d))			\$260.00 =	\$0
				BASIC FEE (37 CFR 1.16(a))	\$690.00
	Total of above Calculations =				\$1122.00
	Reduction by 50% for filing by small entity (Note 37 CFR 1.9, 1.27, 1.28).				
	TOTAL =				\$1122.00

19. Small entity status

- a. ☐ A Small entity statement is enclosed
- b. ☐ A small entity statement was filed in the prior nonprovisional application and such status is still proper and desired.
- c. ☐ Is no longer claimed.


20. ☒ A check in the amount of \$ 1122.00 to cover the filing fee is enclosed.

21. ☐ A check in the amount of \$ \_\_\_\_\_ to cover the recordal fee is enclosed

22. The Commissioner is hereby authorized to credit overpayments or charge the following fees to Deposit Account No. 06-1205:

- a. ☒ Fees required under 37 CFR 1.16.
- b. ☒ Fees required under 37 CFR 1.17
- c. ☐ Fees required under 37 CFR 1.18.

**SIGNATURE OF APPLICANT, ATTORNEY, OR AGENT REQUIRED**

NAME	Leonard P. Diana, Esq. - Reg. No. 28,490
SIGNATURE	
DATE	January 13, 2000

## TITLE OF THE INVENTION

### DATA COMMUNICATION SYSTEM AND METHOD OF DEALING WITH PROBLEMS IN SAID SYSTEM

5

## BACKGROUND OF THE INVENTION

This invention relates to a data communication system and to a method of dealing with problems which arise in this data communication system.

When a problem develops during printing with a printing apparatus connected to a host computer via a prescribed cable so as to be capable of communicating with the host computer, there are occasions where the operator cannot readily ascertain the cause of the problem. For example, if the accompanying operating manual says that three successive beep tones mean that there is not enough ink, no difficulty will arise so long as the operator remembers what measures are to be taken to deal with this situation. However, there are often occasions where the operator does not remember or never memorized what action to take. In such cases the operator cannot determine the cause of the problem unless the pertinent description is found in the operating manual. There are also instances where the manual is not readily available, in which case it is

very difficult to ascertain the cause of the problem.

In systems available for dealing with such problems, a printer driver installed in the host computer displays the causes of simple problems such as  
5 "① Out of Paper", "② Paper Jam", "③ Out of Ink", etc.  
and uses the display of the host computer to tell the operator what measures to take.

However, programming the software of the printer driver to contain measures for all possible problems is  
10 impractical because of limitations imposed by available memory capacity. There are also problems that are difficult for the operator to understand.

Accordingly, for problems that are not so simple, such as when a diode for sensing head temperature fails,  
15 when the voltage for driving a paper-feed motor is inadequate or when it is not possible to introduce power, there are no specifications dealing with countermeasures and the state of the art is such that the operator must call and wait for the arrival of a  
20 serviceman before the cause of the problem can be tracked down. Furthermore, even if the cause is determined, there are occasions where the apparatus cannot be repaired on-site if replacement parts have not been brought.

25

#### SUMMARY OF THE INVENTION

Accordingly, an object of the present invention is to provide a data communication system and a problem management method for this system through which it is possible to analyze the causes of problems in advance.

Another object of the present invention is to provide a system through which the nature of a problem is analyzed and the appropriate countermeasures displayed automatically by a computer that is capable of responding to an inquiry in the proper manner, thereby making it possible to determine the cause of the problem accurately and to deal with the problem quickly in round-the-clock support.

According to the present invention, the foregoing objects are attained by providing a communication system in which an image forming apparatus capable of forming images and a countermeasure specifying computer, which is capable of specifying a countermeasure when a specific event has occurred in the image forming apparatus, are capable of being connected to each other via a communication network, wherein the image forming apparatus includes: storage means for storing identifying information which identifies a countermeasure specifying computer that is capable of specifying a countermeasure when the specific event occurs; sending means for sending specific-event

information concerning the specific event to the  
countermeasure specifying computer that corresponds to  
the identifying information of the countermeasure  
specifying computer stored by the storage means, the  
5 specific-event information being sent when the specific  
event occurs; and answer display means for receiving and  
displaying an answer from this countermeasure specifying  
computer in response to the specific-event information  
sent by the sending means; and the countermeasure  
10 specifying computer includes specifying means for  
analyzing the specific-event information from the image  
forming apparatus and specifying an answer.

By way of example, the specific event is a printer  
problem, the storage means is provided in the printer,  
15 and the sending means and answer display means are  
provided in a printer control computer.

Further, according to the present invention, the  
foregoing objects are attained by providing a  
communication system in which an image forming apparatus  
20 capable of forming images and a countermeasure  
specifying computer, which is capable of specifying a  
countermeasure when a problem has occurred in the image  
forming apparatus, are capable of being connected to  
each other via a communication network, wherein the  
25 image forming apparatus has means for storing  
identifying information which identifies a

countermeasure specifying computer that is capable of specifying a countermeasure when the problem occurs, sending problem information concerning the problem to the countermeasure specifying computer that corresponds  
5 to the stored identifying information of the countermeasure specifying computer when the problem occurs, and receiving and displaying an answer from this countermeasure specifying computer in response to the sent problem information; and the countermeasure  
10 specifying computer includes means for analyzing the problem information from the image forming apparatus and sending back an answer.

By way of example, the image forming apparatus further includes a printer for printing out input  
15 information, and a printer control computer connected to the printer.

Further, by way of example, the printer control computer has countermeasure display means for analyzing the nature of a problem autonomously and displaying a  
20 countermeasure in a case where the problem can be eliminated by a simple operation performed by the operator.

Further, by way of example, the countermeasure specifying computer is a service depot computer.  
25 Alternatively, the countermeasure specifying computer is a service depot computer if the problem is one requiring

maintenance by a serviceman and a customer support computer if the problem is one capable of being eliminated by operator endeavor without requiring assistance of a serviceman.

5           Furthermore, by way of example, the communication network is the Internet communication network, and the identifying information of the countermeasure specifying computer is an Internet mail address.

10           Further, by way of example, a plurality of image forming apparatus are connected to the countermeasure specifying computer.

15           Other features and advantages of the present invention will be apparent from the following description taken in conjunction with the accompanying drawings, in which like reference characters designate the same or similar parts throughout the figures thereof.

#### BRIEF DESCRIPTION OF THE DRAWINGS

20

Fig. 1 is a block diagram illustrating the configuration of a printing system embodying the present invention;

25           Fig. 2 is an external perspective view showing the structure of an ink-jet printer, which is a typical embodiment of an output unit shown in Fig. 1;



Fig. 3 is a block diagram showing the construction of a control circuit for controlling the ink-jet printer;

Fig. 4 is a diagram showing the display screen  
5 examples of the host computer to tell operator what measures to take;

Fig. 5 is a diagram useful in describing examples of answers in a case where a service depot computer of the printer according to this embodiment has been  
10 queried in regard to the nature of a problem;

Fig. 6 is a flowchart useful in describing problem management control at execution of a printing control operation in the system of this embodiment;

Fig. 7 is a flowchart useful in describing problem  
15 management control at execution of a printing control operation in the system of this embodiment;

Fig. 8 is a diagram showing the configuration of a system according to a second embodiment of the present invention; and

20 Fig. 9 is a diagram showing the configuration of a system according to a third embodiment of the present invention.

#### DESCRIPTION OF THE PREFERRED EMBODIMENTS

25

Preferred embodiments of the present invention will

now be described in detail with reference to the drawings.

[First Embodiment]

A preferred embodiment of the present invention will now be described with reference to Fig. 1, which is a block diagram illustrating the configuration of a printing system embodying the present invention. The printing system according to this embodiment includes a host computer 1, a printing apparatus 3, a cable 2 connecting the host computer 1 and the printing apparatus 3, a service depot computer 4, and networks 5 for connecting the host computer 1 to the service depot computer 4 and to a customer support computer 6.

The host computer 1 sends the printing apparatus 3 printing-related information such as print data and a print command using the software of an enabled printer driver and sends the service depot computer 4 or customer support computer 6 problem information, which is information concerning a particular problem.

The printing apparatus 3 executes printing processing in accordance with the printing-related information sent. The printing apparatus 3, which is constituted by a microprocessor system that includes a read-only memory (ROM) and a random-access memory (RAM), functionally comprises the components described below.

Specifically, the printing apparatus 3 has an

interface 11 for exchanging data with the host computer  
1, a pattern expansion unit 12 for expanding data such  
as text and graphics in memory, a font information unit  
13 for storing font information, a control panel 14 used  
5 to set various parameters for controlling printing, and  
a data bus 15. The printing apparatus 3 further  
includes a message notification unit 16 for reporting a  
message from the printing apparatus 3 to the host  
computer 1, a command analyzer 17 for analyzing print  
10 data from the host computer 1 via the cable 2, a  
controller 18 for controlling the overall apparatus, and  
an output unit 19, which comprises, e.g., a ink-jet  
printer, for forming a visible data image on paper.

The controller 18 has a central processing unit  
15 (CPU), a ROM and a RAM and controls the overall  
operation of the printing apparatus 3, such as the  
reading and writing of information.

The pattern expansion unit 12 has a memory  
comprising a RAM capable of being freely read and  
20 written. The command analyzer 17 is expressed in the  
form of hardware but analyzes commands by processing  
software using the CPU of the controller 18. It should  
be noted that the command analyzer 17 may be constituted  
by a decoder instead of relying upon software  
25 processing.

The details of the output unit 19 will now be

described. The output unit 19 may be a laser printer or thermal-transfer printer as well as an ink-jet printer. The output unit 19 may also be a color printer. Further, the output unit 19 is not limited to a bilevel-  
5 output printer and may be a multilevel-output printer.

Fig. 2 is an external perspective view showing the structure of an ink-jet printer IJRA, which is a typical embodiment of the output unit 19 shown in Fig. 1.

In Fig. 2, a carriage HC is engaged with a helical  
10 groove 5004 of a lead screw 5005 rotated via driving force transmission gears 5011, 5009 in operative association with the forward and reverse rotation of a driving motor 5013. The carriage HC has a pin (not shown) moved back and forth in directions of arrows a  
15 and b. An ink-jet cartridge IJC is mounted on the carriage HC. Numerals 5002 denote a paper retaining plate which presses paper against a platen 5000 along the traveling direction of the carriage. Numerals 5007, 5508 denotes photocouplers which constitute home  
20 position sensing means for verifying the presence of a carriage lever 5006 in the vicinity of the photocouplers and changing over the direction in which the motor 5013 is rotated. Numerals 5016 denote a member which supports a cap member 5022, which is for capping the  
25 front side of the recording head. Numerals 5015 denote suction means for applying suction to the cap to subject

the cap to suction recovery via an opening 5023 inside the cap. Numerals 5019 denote a member which makes it possible to move a cleaning blade 5017 back and forth.

The cleaning blade 5017 and the member 5019 are

5 supported on a support plate 5018. It goes without saying that the blade need not be of this type and that a well-known cleaning blade can be applied to this example. Numeral 5021 denotes a lever for starting the suction of the suction recovery operation. The lever  
10 moves with movement of a cam 5020 engaged with the carriage. Movement is controlled by well-known transfer means whereby the driving force from the driver motor is changed over as by a clutch.

The capping, cleaning and suction recovery  
15 operations are so arranged that the desired processing is performed at the corresponding positions by the action of the lead screw 5005 when the carriage arrives in an area on the home-position side. However, if it is so arranged that the desired operations are performed at  
20 well-known timings, this arrangement can also be applied to this example.

The present invention is described in regard to a printing apparatus particularly of the ink-jet printing type, in which the apparatus is equipped with means  
25 (e.g., an electrothermal transducer or laser beam mechanism) for generating thermal energy as the energy

utilized to discharge ink, wherein a change in the state of the ink is brought about by this thermal energy.

With regard to a typical configuration and operating principle, it is preferred that the foregoing  
5 be achieved using the basic techniques disclosed in the specifications of USP 4,723,129 and 4,740,796. This scheme is applicable to both so-called on-demand-type and continuous-type apparatus. In the case of the on-demand type, at least one drive signal, which provides a  
10 sudden temperature rise that exceeds that for film boiling, is applied, in accordance with printing information, to an electrothermal transducer arranged to correspond to a sheet or fluid passageway holding a fluid (ink). As a result, thermal energy is produced in  
15 the electrothermal transducer to bring about film boiling on the thermal working surface of the ink-jet head. Accordingly, air bubbles can be formed in the fluid (ink) in one-to-one correspondence with the drive signals. Owing to growth and contraction of the air  
20 bubbles, the fluid (ink) is jetted via an orifice so as to form at least one droplet. If the drive signal has the form of a pulse, growth and contraction of the air bubbles can be made to take place rapidly and in appropriate fashion. This is preferred since it will be  
25 possible to achieve fluid (ink) discharge exhibiting excellent response.

Signals described in the specifications of USP  
4,463,359 and 4,345,262 are suitable as drive pulses  
having this pulse shape. It should be noted that even  
better printing can be performed by employing the  
5 conditions described in the specification of USP  
4,313,124, which discloses an invention relating to the  
rate of increase in the temperature of the above-  
mentioned thermal working surface.

In addition to the combination of the orifice,  
10 fluid passageway and electrothermal transducer (in which  
the fluid passageway is linear or right-angled)  
disclosed as the construction of the print head in each  
of the above-mentioned specifications, an arrangement  
using the art described in the specifications of USP  
15 4,558,333 and 4,459,600, which disclose elements  
disposed in an area in which the thermal working portion  
is curved, may be employed. Further, it is possible to  
adopt an arrangement based upon Japanese Patent  
Application Laid-Open No. 59-123670, which discloses a  
20 configuration having a common slot for the ink discharge  
portions of a plurality of electrothermal transducers,  
or Japanese Patent Application Laid-Open No. 59-138461,  
which discloses a configuration having openings made to  
correspond to the ink discharge portions, wherein the  
25 openings absorb pressure waves of thermal energy.

As a print head of the full-line type having a

length corresponding to the maximum width of the  
printing medium capable of being printed on by the  
printing apparatus, use can be made of an arrangement in  
which the length is satisfied by a combination of plural  
5 print heads of the kind disclosed in the foregoing  
specifications, or an arrangement in which print heads  
serve as a single integrally formed print head.

The print head may be of the replaceable tip-type,  
in which the electrical connection to the apparatus  
10 proper and the supply of ink from the apparatus proper  
can be achieved by mounting the head on the apparatus  
proper, or of the cartridge type, in which the print  
head itself is integrally provided with an ink tank.

In order to make the effects of printing much more  
15 stable, it is preferred that the printing apparatus of  
the present invention be additionally provided with  
print head recovery means and auxiliary means, etc.  
Specific examples are print head capping means, cleaning  
means, pressurizing or suction means, preheating means  
20 comprising an electrothermal transducer, a heating  
element separate from this transducer or a combination  
of the transducer and the heating element, and a pre-  
discharge mode for performing a discharge of ink  
separate from a discharge for printing. These  
25 expedients are effective in achieving stable printing.

The printing mode of the printing apparatus is not



limited to a printing mode solely for the mainstream colors such as black and white. The apparatus adopted can be one equipped with at least one print head for a plurality of different colors or one full-color print head using mixed colors, through it is desired that this be achieved by a print head having an integrated structure or by a combination of a plurality of print heads.

Further, the embodiment of the present invention set forth above is described on the assumption that ink is the fluid. The ink used may be one which solidifies at room temperature or lower, one which softens at room temperature or one which is a liquid at room temperature. In general, temperature control is performed in such a manner that ink viscosity will fall within a stable ink jetting range by adjusting the temperature of the ink itself so as to fall within a temperature range of no less than 30°C to no greater than 70°C. Accordingly, it will suffice to use an ink liquefied when the printing signal is applied.

In order to positively prevent elevated temperature due to thermal energy by using this as the energy for converting the ink from the solid state to the liquid state, or in order to prevent evaporation of the ink, it is permissible to use an ink which solidifies when left standing but which is liquefied by application of heat.

In any case, ink which is liquefied for the first time by thermal energy, such as an ink liquefied by application of thermal energy conforming to a printing signal and jetted as a liquid ink, or ink which has  
5 already begun to solidify at the moment it reaches the printing medium, can be applied to the present invention. Such inks may be used in a form in which they oppose the electrothermal transducer in a state in which they are held as a liquid or solid in the recesses  
10 or through-holes of a porous sheet, as described in Japanese Patent Application Laid-Open Nos. 54-56847 and 60-71260. In the present invention, the most effective method of dealing with these inks is the above-described method of film boiling.

15 A printing apparatus according to the present invention may take on a variety of forms. It may be provided as an integral part of or separate from an information processing device such as a computer and serve as the image output terminal thereof, as a copier  
20 apparatus in combination with a reader or the like, or as a facsimile machine having sending and receiving functions.

The components of the controller 18 shown in Fig. 1 will be described with reference to Fig. 3, which is a  
25 block diagram showing the details of the controller 18 illustrated in Fig. 1.

As shown in Fig. 3, the controller 18 includes a central processing unit (CPU) 101, a read-only memory (ROM) 102, a random-access memory (RAM) 103, an interface (I/F) 104 and a local data bus 115. The controller 18 further includes a paper sensor 105, a head sensor 106, a cover sensor 107, a paper-jam sensor 108, an ink-jet ink sensor 109, a sensor 110 for sensing power-supply voltage (5 V) of the controller, a sensor 111 for sensing monitor voltage ( $V_M$ ), a sensor 112 for sensing head voltage ( $V_H$ ), a sensor 113 for sensing ambient temperature ( $T_a$ ), a sensor 114 for sensing head temperature ( $T_H$ ), and a data bus 116 for connecting each sensor with the interface 104.

The sensor 110 for sensing power-supply voltage (5 V) of the controller, the sensor 111 for sensing monitor voltage ( $V_M$ ) and a sensor 112 for sensing head voltage ( $V_H$ ) sense the respective power-supply voltages of the printing apparatus 3.

The command structure which controls the printing apparatus 3 is stored in the ROM 102. When a power switch (not shown) is closed, the stored content of the ROM 102 is read out and decoded under the control of the CPU 101, whereby the printing apparatus begins operating.

The ROM 102 also contains addresses of inquiry destinations for when problems occur, and codes that are

classified by level of the problem. For example, the address of a printer service depot computer is stored in the ROM 102 beforehand as an inquiry destination for when a problem occurs.

5       According to this embodiment, and by way of example, an Internet mail address is adopted as the inquiry destination, with the following address information being stored in the form of an ASCII code:

          http/www.design.service.co.jp       ... (1)

10       Among the problems sensed by the sensors 105 to 109 of the printing apparatus 3, there are certain simple problems that the operator of the apparatus can readily deal with to effect recovery, such as the sensing of "PAPER LOADED?", "HEAD MOUNTED?" and "COVER OPEN OR  
15   CLOSED" and problems such as "PAPER JAM DURING OPERATION" and "OUT OF INK". For these simple problems, control is exercised in such a manner that the problems are displayed on the display of the host computer 1 by the printer driver in the same way as in the prior art.  
20   An example of such a display is illustrated in Fig. 4.

      By observing the display shown in Fig. 4 on the display of the host computer 1, the operator can identify the cause of the problem, eliminate the cause and then start the printing operation again. The  
25   operator is allowed to take the proper measures upon checking the display on the host computer even if the

operator contacts a serviceman.

However, there are problems, even if they are displayed on the display of the host computer 1 using the printer driver, for which there are no

5 countermeasures that can be taken by the operator.

These are problems capable of being sensed by the sensors 110 to 114, namely whether the "5 V voltage", "V<sub>M</sub> voltage" and "V<sub>H</sub> voltage" are normal or not, whether the ambient temperature T<sub>a</sub> is too high or too low and  
10 whether the head temperature T<sub>H</sub> is normal or not.

There are other problems besides these and they are too numerous to cite here. If a countermeasures program run by the printer driver of the host computer 1 were included to cope with all of these problems, an enormous  
15 memory capacity would be required and the operator would be confronted with a very laborious operation.

In the event of a problem from which it is difficult for the operator to effect recovery, such as a problem sensed by any of the sensors 110 to 114, the  
20 printer driver is notified of problem detection by any of the sensors 110 to 114 and causes a mail address of the kind indicated by (1) above, which has been stored in the ROM, to be displayed on the display of the host computer 1.

25 The operator observes the display, effects a connection to the Internet and queries the printer

service depot computer about the nature of the problem.

The service depot computer judges that the relevant problem codes are 110, 111, 112, ... and displays answers on the display of the host computer 1 via the network 5 to indicate the cause of the problem.

An example of the answers is shown in Fig. 5. In this example, the types of problems are into types A, B and C.

A problem of Type A is capable of being resolved by the operator per se, a problem of Type B is technical and cannot be resolved by the operator per se, and a problem of Type C relates to a question the operator wishes to inquire about.

Internet addresses (website URLs) specify transfer destinations, which depend upon the problem type.

For problems of Type A, the answer can be provided by the printer driver in a manner similar to that of the prior art, as shown in Fig. 4, and therefore transfer-destination address is displayed (i.e., "NONE" is displayed).

For problems of Type B, the following mail address of the service depot computer 4:

`http://www.design.service.co.jp` ... (2)

is displayed according to the example of Fig. 5, and for problems of Type C, the following mail address of the customer support computer 9:

http://www.customer.service.co.jp ... (3)

is displayed according to the example of Fig. 5.

Thus, the destination address that conforms to the nature of the particular problem is displayed.

5 In the example of the problem codes shown in Fig. 5, answers are classified depending upon the nature of the problem in the manner described below.

[Relationship between examples of displays shown in Fig. 5 and content stored in ROM 102]

10 When paper fails to be fed or printing fails to be performed owing to an abnormal  $V_M$  (motor voltage), for example, the CPU senses information 111 from the interface 104, reads the corresponding problem-code information [indicated by (4) below] out of the ROM 102  
15 and sends this information to the host computer.

The following information:

B (problem type) http://www.design.service.co.jp  
(Internet address) 111 ... (4)

has been stored in the ROM 102 as an example of content  
20 in the form of an ASCII code, by way of example.

After receiving the information indicated by (4) above, the program of the printer driver that has been installed in the host computer 1 analyzes the information, displays the result of analysis on the  
25 computer display screen and seeks a decision from the operator as to whether or not the service depot ("design

service") is to be queried.

If consent is obtained, the printer driver sends the problem code 111 to the service depot ("design service") department indicated by (2) above, obtains the  
5 reply, which is the result provided by the service depot ("design service") department, from the service depot computer 4 and displays the reply on the display to notify the operator.

In this case, for example, "NO MOTOR VOLTAGE. TAKE  
10 PRINTER TO SERVICE DEPOT." is displayed.

In the case of the problem codes 115 to 117, these codes are sent to the customer support ("customer service") computer 6. The latter refers to a program that has been installed in this computer, deduces the  
15 answers that correspond to the problem codes and automatically sends the answers back to the host computer 1 that originally issued the problem codes 115 to 117.

Reference will now be had to Figs. 6 and 7 to  
20 describe control of the overall operation of the system according to this embodiment. Figs. 6 and 7 are useful in describing problem management control at execution of a printing control operation in the system of this embodiment.

25 Preconditions for control are that the host computer 1, service depot computer 4, customer support

⋮



computer 6 and printing apparatus 3 be connected by the network 5 and cable 2 and that each of these units be supplied with power, as indicated at step S101 in Fig. 6.

5           When power has been introduced, each unit is initialized at step S102. This initialization processing is executed in accordance with a program incorporated in each unit.

10           Next, at step S103, the host computer 1, service depot computer 4, customer support computer 6 and printing apparatus 3 attain the usual standby state. In this state the host computer 1 waits for the operator to issue a print command (i.e., to perform a print operation) at steps S103 and S104. For example, the  
15           host computer 1 waits for the operator to operate a word processor application (e.g., Microsoft Word), create a document and then perform a printout operation.

20           When the operator of the host computer 1 issues a print command, control proceeds from step S104 to step S105, at which the printing apparatus 3 performs printing. Next, at step S106, the printing apparatus 3 determines whether printing ended normally. If the decision rendered is "YES", control proceeds to step S117, at which the printing apparatus 3 ejects the  
25           normal printed image. Control then returns to step S103.

On the other hand, if the decision rendered at step S106 is that the printing apparatus 3 did not end printing normally, control proceeds to step S107. Here the host computer 1 accepts the problem classification information from the printing apparatus 3. If the problem is not of Type A, control proceeds to step S108.

The host computer 1 determines whether the problem type from the printing apparatus 3 is Type B or not. If the problem is of Type B, control proceeds to step S109, at which the host computer 1 displays the message "THIS PROBLEM REQUIRES THAT YOU CONTACT THE SERVICE DEPOT ('design service') DEPARTMENT" on the display to notify the operator.

This is followed by step S110, at which the operator observes the display of step S109 and decides whether to make an inquiry concerning the problem. If the operator decides not to make an inquiry, control returns to step S103 and the operator does not take immediate measures to deal with the problem.

If the operator decides to make an inquiry at step S110, on the other hand, an indication to this effect is entered. As a result, control proceeds from step S110 to step S111, where the host computer 1 reads out the website address of the service depot computer 4 and sends the problem codes 110 to 114 to this address (<http://www.design.service.co.jp>) via the network 5.

Next, at step S112, the service depot computer 4 receives any or all of the problem codes 110 to 114 sent from the host computer 1. The service depot computer 4 analyzes the nature of the problem codes 110 to 114 at  
5 step S113 in accordance with analytical program of the computer.

This is followed by step S114, at which the service depot computer 4 sends the analytical result of step S113 to the host computer 1, which is linked to it via  
10 the network 5, automatically in accordance with an answer program.

The host computer 1 displays the answer sent at step S115 on its display (see the problems of Type B shown in Fig. 5).

15 By way of example, the following is displayed as an example of an answer in a case where the problem code 110 is sensed by the sensor 110 for sensing power-supply voltage (5 V) of the controller:

"NO 5V DC VOLTAGE. TAKE PRINTER TO SERVICE DEPOT."

20 The operator checks the answer display provided at step S115 and deals with the problem, such as by taking the printing apparatus 3 to a repair store, as indicated at step S116. Alternatively, the operator requests on-site repair as by calling a serviceman. In this case  
25 also the analysis of the nature of the problem ends, as a result of which the appropriate repairs can be made in

prompt fashion.

If the problem is found to be of Type A at step S107, control proceeds to step S118, at which the software application of the printer driver automatically judges whether the problem is any of the problem codes 105 to 109 and causes a screen whose content conforms to the problem code to be displayed on the display of the host computer 1. This processing is executed by the host computer 1 alone.

10       The operator performs an operation at step S119 that is in accordance with the indication on the display screen displayed at step S118.

By way of example, if "NO PAPER" or "CANCEL PRINTING?" is displayed, the operator loads paper or  
15       performs an operation to cancel printing, thereby eliminating the problem.

Next, at step S120, the host computer 1 waits for the operator to take appropriate measures. If such measures have been taken, control proceeds to step S121,  
20       at which the printing apparatus 3 exercises control conforming to the measures taken, as by ejecting the printout of the normal image or canceling printing and then terminating operation. Control then returns to step S103.

25       In a case where the type of problem from the printing apparatus 3 is found not to be Type B at step

S108, control proceeds to step S122 on the assumption that the problem is of Type C. At this step the host computer 1 determines whether the problem is of Type C. If the information is temporary in nature, such as  
5 noise, it is judged that a sensing error has occurred and, hence, control returns to step S103.

On the other hand, if the decision rendered at step S122 is that the problem is of Type C, control proceeds to step S123, where the host computer 1 displays the  
10 message "THIS PROBLEM REQUIRES THAT YOU CONTACT THE CUSTOMER SUPPORT DEPARTMENT ('Customer Service Department')" on the display to notify the operator.

This is followed by step S124, at which the operator observes the display of step S123 and decides  
15 whether to make an inquiry concerning the problem. If the operator decides not to make an inquiry, control returns to step S103 and the operator does not take immediate measures to deal with the problem.

If the operator agrees to make an inquiry at step  
20 S124, on the other hand, control proceeds to step S125, at which the problem codes 115 to 117 of Type C are sent to the customer support computer 6 (to the mail address <http://www.customer.service.co.jp>).

The customer support computer 6 receives the  
25 information of problem type C via the network 5 at step S126.

The customer support computer 6 analyzes the received problem codes 115 to 117 at step S127. This is followed by step S128, at which the customer support computer 6 automatically extracts the corresponding answer, on the basis of application software within the customer support computer 6, in accordance with the problem code that was analyzed at step S127, and transfers the answer to the host computer 1 that originally sent the problem codes 115 to 117.

10 The host computer 1 causes the answer that has been sent to it via the network 5 to be displayed on its display at step S129. Control then proceeds to step S130, at which the operator observes the answer from the customer support computer 6 displayed on the display of  
15 the host computer 1 and then deals with the problem. Control thenceforth returns to step S103.

Thus, in accordance with this embodiment, as described above, the nature of a problem can be analyzed automatically and a reply made to the operator, as a  
20 result of which appropriate measures can be taken. Further, the cause of a problem can be judged in accurate fashion and it is possible to realize a troubleshooting system that requires low labor cost. In addition, problems can be dealt with rapidly on a round-  
25 the-clock basis.

In the foregoing description, inquiries concerning

problems are divided between a service depot computer and a customer support computer. The service depot computer is queried with regard to problems relating to the basic components of the machine, namely problems requiring maintenance by a serviceman. In a case where, depending upon the measures taken by the customer, it is possible for the customer to solve the problem himself without the assistance of a serviceman, the customer support computer is queried in regard to the nature of the problem. However, if as a result of querying one of these computers it is judged that more appropriate support can be obtained by querying the other computer, a message to this effect may be displayed in the answer given.

Further, the nature of a problem can be analyzed reliably and in automatic fashion and the appropriate countermeasure can be indicated to the operator. Since this indication can be made automatically on the computer side, there is no longer any limitation upon time that support is available. For example, 24-hour support can be provided. In this case also the depot computers 4 and 6 or the host computer 1 can be provide support automatically. This makes possible a troubleshooting system with low labor costs, in which it is unnecessary for personnel to stand by waiting for an inquiry.

Furthermore, by providing a printer with computer address information, the operator can be reliably notified of the computer site that can best deal with the printer problem. This makes it possible to cope  
5 with problems in suitable fashion.

[Second Embodiment]

The first embodiment described above illustrates an example of a case where is only one combination of a host computer 1 and a printer 3 connected to it by a  
10 cable. However, the present invention is not limited to such an example, for a plurality of combinations of the host computer 1 and printing apparatus 3 connected by the cable 2 may be provided.

Reference will be had to Fig. 8 to describe a  
15 second embodiment of the invention in which there are a plurality of combinations of the host computer 1 and printing apparatus 3 connected by the cable 2. Fig. 8 is a diagram showing the configuration of a system according to a second embodiment of the present  
20 invention.

As shown in Fig. 8, there are three combinations of host computers and printers connected to them by cables, namely a host computer 1a and a printer 3a connected by a cable 2a, a host computer 1b and a printer 3b  
25 connected by a cable 2b, and a host computer 1c and a printer 3c connected by a cable 2c. Support can of



course be provided in exactly the same manner in this case as well.

In this case, it will suffice if each combination of host computer and printer connected via a cable is provided with functions similar to those of the host computer 1 and printing apparatus 3 connected via cable 2 illustrated in Fig. 1 of the first embodiment.

In accordance with the second embodiment, as described above, actions and effects similar to those of the first embodiment are obtained even if there are a large number of combinations of host computers and printers connected to them by cables.

Although an example in which there are three combinations of host computers and printers connected to them by cables has been described in conjunction with Fig. 8, the number of combinations is not limited to three and any number of combinations may be provided as a matter of course.

#### [Third Embodiment]

In the foregoing description, inquiries concerning problems are divided between a service depot computer and a customer support computer. The service depot computer is queried with regard to problems relating to the basic components of the machine, namely problems requiring maintenance by a serviceman. In a case where, depending upon the measures taken by the customer, it is

possible for the customer to solve the problem himself without the assistance of a serviceman, the customer support computer is queried in regard to the nature of the problem. However, the present invention is not  
5 limited to this example, for problems may be dealt with solely by, e.g., the service depot computer without dividing computers between the service depot computer and the customer support computer. The aforementioned problems can be dealt with by providing solely the depot  
10 computer with a powerful troubleshooting program.

Fig. 9 illustrates a third embodiment of the present invention adapted to deal with problems using only a service depot computer.

In the third embodiment shown in Fig. 9, problems  
15 that can be dealt with by the host computers 1a, 1b and 1c are handled by the host computers 1a, 1b and 1c. In the case of problems of Types B and C mentioned in the first embodiment, the website address of the service depot computer 4 is read out and the problem codes 110  
20 to 114 and problem codes 115 to 117 are sent to the website address (<http://www.design.service.co.jp>) of the service depot computer 4 together via the network 5.

Thus, in accordance with the third embodiment as described above, actions and effects similar to those of  
25 the first embodiment are obtained solely with the service depot computer.

[Other Embodiments]

The present invention can be applied to a system constituted by a plurality of devices (e.g., a host computer, interface, reader, printer, etc.) or to an apparatus comprising a single device (e.g., a copier or facsimile machine, etc.).

Furthermore, it goes without saying that the object of the invention is attained by supplying a storage medium storing the program codes of the software for performing the functions of the foregoing embodiments to a system or an apparatus, reading the program codes with a computer (e.g., a CPU or MPU) of the system or apparatus from the storage medium, and then executing the program codes.

In this case, the program codes read from the storage medium implement the functions of the above-described embodiments, and the storage medium storing the program codes constitutes the invention.

Further, the storage medium, such as a floppy disk, hard disk, optical disk, magneto-optical disk, CD-ROM, CD-R, magnetic tape, non-volatile type memory card or ROM can be used to provide the program codes.

Furthermore, besides the case where the aforesaid functions according to the embodiments are implemented by executing the program codes read by a computer, it goes without saying that the present invention covers a

case where an operating system or the like running on the computer performs a part of or the entire process in accordance with the designation of program codes and implements the functions according to the embodiments.

5           It goes without saying that the present invention further covers a case where, after the program codes read from the storage medium are written in a function expansion board inserted into the computer or in a memory provided in a function expansion unit connected  
10 to the computer, a CPU or the like contained in the function expansion board or function expansion unit performs a part of or the entire process in accordance with the designation of program codes and implements the function of the above embodiment.

15           In a case where the present invention is applied to the above-mentioned storage medium, program code corresponding to the flowcharts described earlier are stored on the storage medium.

          Thus, in accordance with the present invention, as  
20 described above, the nature of a specific event can be analyzed reliably and in automatic fashion and the appropriate countermeasure can be indicated to the operator. Since this indication can be made automatically on the side of the information processing  
25 apparatus, there is no longer any limitation upon time that support is available. For example, 24-hour support

can be provided. In this case also the information processing apparatus can be provide support automatically, thereby making it possible to achieve a troubleshooting system having low labor cost.

5 Further, by providing the information processing apparatus with information regarding a site where analysis is available, the operator can be reliably notified of the analysis site that can deal properly with a specific event that occurred in the information  
10 processing apparatus.

As many apparently widely different embodiments of the present invention can be made without departing from the spirit and scope thereof, it is to be understood that the invention is not limited to the specific  
15 embodiments thereof except as defined in the appended claims.

WHAT IS CLAIMED IS:

1. A communication system in which an image forming  
apparatus capable of forming images and a countermeasure  
specifying computer, which is capable of specifying a  
5 countermeasure when a specific event has occurred in the  
image forming apparatus, are capable of being connected  
to each other via a communication network, wherein said  
image forming apparatus includes:

storage means for storing identifying information  
10 which identifies a countermeasure specifying computer  
that is capable of specifying a countermeasure when the  
specific event has occurred;

sending means for sending specific-event  
information concerning the specific event to the  
15 countermeasure specifying computer that corresponds to  
the identifying information of the countermeasure  
specifying computer stored by said storage means, the  
specific-event information being sent when the specific  
event has occurred; and

20 answer display means for receiving and displaying  
an answer from said countermeasure specifying computer  
in response to the specific-event information sent by  
said sending means; and

said countermeasure specifying computer includes  
25 specifying means for analyzing the specific-event  
information from said image forming apparatus and

specifying an answer.

2. The system according to claim 1, wherein said image forming apparatus further includes:

a printer for printing out input information; and

5 a printer control computer connected to said printer.

3. The system according to claim 1, wherein said printer control computer has countermeasure display means for analyzing the nature of a problem autonomously  
10 and displaying a countermeasure in a case where the problem can be eliminated by a simple operation performed by the operator.

4. The system according to claim 1, wherein the specific event is a printer problem, said storage means  
15 is provided in the printer, and said sending means and said answer display means are provided in said printer control computer.

5. The system according to claim 4, wherein said printer control computer has countermeasure display  
20 means for analyzing the nature of a problem autonomously and displaying a countermeasure in a case where the problem can be eliminated by a simple operation performed by the operator.

6. The system according to claim 1, wherein said  
25 countermeasure specifying computer is a service depot computer.

7. The system according to claim 1, wherein said countermeasure specifying computer is a service depot computer if the problem is one requiring maintenance by a serviceman and a customer support computer if the problem is one capable of being eliminated by operator endeavor without requiring assistance of a serviceman.

8. The system according to claim 1, wherein said communication network is the Internet communication network, and the identifying information of said countermeasure specifying computer is an Internet mail address.

9. The system according to claim 1, wherein a plurality of image forming apparatus are connected to the countermeasure specifying computer.

10. A method of dealing with problems in a communication system in which an image forming apparatus capable of forming images and a countermeasure specifying computer, which is capable of specifying a countermeasure when a problem has occurred in the image forming apparatus, are capable of being connected to each other via a communication network, wherein:

said image forming apparatus stores identifying information which identifies a countermeasure specifying computer that is capable of specifying a countermeasure when the problem has occurred, sends problem information concerning the problem to the countermeasure specifying



computer that corresponds to the stored identifying  
information of the countermeasure specifying computer  
when the problem has occurred, and receives and displays  
an answer from said countermeasure specifying computer  
5 in response to the sent problem information; and

said countermeasure specifying computer analyzes  
the problem information from said image forming  
apparatus and sends back an answer.

11. The method according to claim 10, wherein said  
10 image forming apparatus includes:

a printer for printing out input information; and  
a printer control computer connected to said  
printer.

12. The method according to claim 11, wherein said  
15 printer control computer analyzes the nature of a  
problem autonomously and displays a countermeasure in a  
case where the problem can be eliminated by a simple  
operation performed by the operator.

13. The method according to claim 10, wherein said  
20 countermeasure specifying computer is a service depot  
computer.

14. The method according to claim 10, wherein said  
countermeasure specifying computer is a service depot  
computer if the problem is one requiring maintenance by  
25 a serviceman and a customer support computer if the  
problem is one capable of being eliminated by operator

endeavor without requiring assistance of a serviceman.

15. The method according to claim 10, wherein said communication network is the Internet communication network, and the identifying information of said

5 countermeasure specifying computer is an Internet mail address.

16. The method according to claim 10, wherein a plurality of image forming apparatus are connected to the countermeasure specifying computer.

10 17. A computer program sequence in a communication system in which an image forming apparatus capable of forming images and a countermeasure specifying computer, which is capable of specifying a countermeasure when a specific event has occurred in the image forming  
15 apparatus, are capable of being connected to each other via a communication network, wherein the program sequence implements the following steps in said image forming apparatus:

a storage step of storing identifying information  
20 which identifies a countermeasure specifying computer that is capable of specifying a countermeasure when the specific event has occurred;

a sending step of sending specific-event information concerning the specific event to the  
25 countermeasure specifying computer that corresponds to the identifying information of the countermeasure

specifying computer stored at said storage step, the specific-event information being sent when the specific event has occurred; and

an answer display step of receiving and displaying  
5 an answer from said countermeasure specifying computer in response to the specific-event information sent at said sending step;

and implements the following step in said countermeasure specifying computer:

10 a specifying step of analyzing the specific-event information from said image forming apparatus and specifying an answer.

18. A computer program sequence in a communication system in which an image forming apparatus capable of  
15 forming images and a countermeasure specifying computer, which is capable of specifying a countermeasure when a problem has occurred in the image forming apparatus, are capable of being connected to each other via a communication network, wherein the program sequence  
20 implements the following step in said image forming apparatus:

a step of storing identifying information which identifies a countermeasure specifying computer that is capable of specifying a countermeasure when the problem  
25 has occurred, sending problem information concerning the problem to the countermeasure specifying computer that

corresponds to the stored identifying information of the countermeasure specifying computer when the problem has occurred, and receiving and displaying an answer from said countermeasure specifying computer in response to  
5 the sent problem information;

and implements the following step in said countermeasure specifying computer:

a step of analyzing the problem information from said image forming apparatus and sending back an answer.

10 19. A computer-readable storage medium storing the computer program sequence described in claim 17.

20. A computer-readable storage medium storing the computer program sequence described in claim 18.

#### New Claims:

15 21. The system according to claim 1, wherein the specifying information includes a plurality of Internet addresses corresponding to types of problems.

22. The method according to claim 10, wherein the specifying information includes a plurality of Internet  
20 addresses corresponding to types of problems.

23. A peripheral device connected to a host apparatus, comprising:

storage means for storing a plurality of Internet addresses corresponding to types of problems; and

25 output means for outputting an Internet address, which corresponds to a problem that has occurred, to

said host apparatus.

24. The peripheral device according to claim 23,  
wherein said peripheral device includes a printer, and  
said host apparatus includes a computer.

5 25. The peripheral device according to claim 23,  
wherein said output means outputs information indicative  
of the type of problem.

26. The peripheral device according to claim 23,  
wherein the problems include a problem which requires  
10 maintenance by a serviceman and a problem which can be  
eliminated by a user himself.

27. A host apparatus connected to a peripheral device,  
comprising:

input means for inputting, from the peripheral  
15 device, an Internet address corresponding to a problem  
that has occurred in said peripheral device; and

display means, which is connected to the Internet  
based upon the Internet address that has been input from  
said input means, for displaying a method of dealing  
20 with the problem.

28. The host apparatus according to claim 27, wherein  
said peripheral device includes a printer, and said host  
apparatus includes a computer.

29. The host apparatus according to claim 27, wherein  
25 the problems include a problem which requires  
maintenance by a serviceman and a problem which can be

eliminated by a user himself.

30. The host apparatus according to claim 27, further comprising means for displaying the Internet address that has been input from said input means;

5        wherein if an Internet connection is specified by a user after the Internet address is displayed, said display means is connected to the Internet based upon the Internet address and is caused to display the method of dealing with the problem.

10      31. The host apparatus according to claim 27, wherein said input means inputs information, which is indicative of the type of problem, together with the Internet address corresponding to the problem that has occurred in said peripheral device; and


15        said display means is connected to the Internet based upon the Internet address that has been input by said input means and displays a method of dealing with the problem based upon the information indicative of the type of problem that has been input by said input means.

20


# ABSTRACT OF THE DISCLOSURE

Disclosed is a system through which the nature of a problem in an apparatus is analyzed and the appropriate countermeasures displayed automatically by a computer that is capable of responding to an inquiry in the proper manner, thereby making it possible to determine the cause of the problem accurately and to deal with the problem quickly in round-the-clock support. A printer includes a controller having an internal store of information concerning sites to which inquiries regarding printer problems may be directed. A service depot computer is queried with regard to printer problems requiring maintenance by a serviceman. In a case where, depending upon the measures taken by the customer, it is possible for the customer to solve the problem himself without the assistance of a serviceman, a customer support computer is queried in regard to the nature of the problem. A message concerning countermeasures is received from the service depot computer or customer support computer and is displayed on a host computer. In a case where the problem can be dealt with through a simple operation, the host computer itself analyzes the nature of the problem and displays the countermeasures.

# FIG. 1







## FIG. 2




**FIG. 3**

FIG. 4





**FIG. 6**


**FIG. 7**

FIG. 8





FIG. 9





**COMBINED DECLARATION AND POWER OF ATTORNEY  
FOR PATENT APPLICATION  
(Page 1)**

As a below named inventor, I hereby declare that: HITOSHI YANAGAWA

My residence, post office address and citizenship are as stated below next to my name.

I believe I am the original, first and sole inventor of the subject matter which is claimed and for which a patent is sought on the invention entitled DATA COMMUNICATION SYSTEM AND METHOD OF DEALING WITH PROBLEMS IN SAID SYSTEM

the specification of which ☒ is attached hereto ☐ was filed on \_\_\_\_\_ as United States Application No. \_\_\_\_\_ and was amended on \_\_\_\_\_ (if applicable).

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to patentability as defined in 37 CFR §1.56

I hereby claim foreign priority benefits under 35 U.S.C. §119(a)-(d) or §365(b), of any foreign application(s) for patent or inventor's certificate, or §365(a) of any PCT international application which designates at least one country other than the United States, listed below and have also identified below any foreign application for patent or inventor's certificate, or PCT international application having a filing date before that of the application on which priority is claimed:

<u>Country</u>	<u>Application No.</u>	<u>Filed (Day/Mo./Yr.)</u>	<u>(Yes/No)</u> <u>Priority Claimed</u>
Japan	11-014899	22 January 1999	Yes

I hereby claim the benefit under 35 U.S.C. § 120 of any United States application(s), or § 365(c) of any PCT international application designating the United States, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT international application in the manner provided by the first paragraph of 35 U.S.C. § 112, I acknowledge the duty to disclose information which is material to patentability as defined in 37 C.F.R. § 1.56 which became available between the filing date of the prior application and the national or PCT international filing date of this application.

<u>Application No.</u>	<u>Filed (Day/Mo./Yr.)</u>	<u>Status (Patented, Pending, Abandoned)</u>
------------------------	----------------------------	--

I hereby appoint the practitioners associated with the firm and Customer Number provided below to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith, and direct that all correspondence be addressed to the address associated with that Customer Number:

**FITZPATRICK, CELLA, HARPER & SCINTO**  
**Customer Number: 05514**

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Full Name of Sole or First Inventor HITOSHI YANAGAWA

Inventor's signature \_\_\_\_\_

Date \_\_\_\_\_ Citizen/Subject of Japan

Residence 46-2, Chuo 1-chome, Nakano-ku, Tokyo, Japan

Post Office Address c/o CANON KABUSHIKI KAISHA

30-2, Shimomaruko 3-chome, Ohta-ku, Tokyo, Japan